

RECESSED CEILING LUMINAIRE

DE95 DCC



3



with louvers



with icecrystal diffuser

CEILING LUMINAIRE FOR RECESSED INSTALLATION
IN PANEL CEILINGS (DAMPA DCC300)

Design	According to rules of maritime classification societies and relevant standards
Housing	Galvanized steel, powder coated white (RAL9016)
Diffuser	Clear polycarbonate with ice crystal or prismatic structure or parabolic louvers
Mounting	Mounting brackets and side rails
Cable entry	2 inlets for cables max. Ø 11 mm
Protection class	IP20 / IP44 in conjunction with ceiling, IP20 with louvers
Voltage	220-240 V AC
Frequency	50-60 Hz

LED SOLUTION

DE95 DCC S	5111009400-xxx
DE95 DCC L	5111009500-xxx
Light source	Linear LP LED modules
Wattage	Max. 20 W / max. 40 W
CCT (color)	3,000 K or 4,000 K
Luminous flux	DE95 DCC S: 1,500 lm DE95 DCC L: 3,100 lm
CRI	≥ 80
Weight	6.6 kg (DE95 DCC S) 9.1 kg (DE95 DCC L)

FLUORESCENT SOLUTION

DE95 DCC 2x 18 W	5111007300-xxx
DE95 DCC 2x 36 W	5111007400-xxx
Light source	T8 fluorescent tubes (not included)
Wattage	2x 18 W 2x 36 W
Weight	6.6 kg (DE95 DCC 2x 18 W) 9.1 kg (DE95 DCC 2x 36 W)

SPARE PARTS

PART NO.

Ice crystal cover (DE95 DCC S)	7931001300
Ice crystal cover (DE95 DCC L)	7931001400

★ EXTRAS

- > 120 V AC execution
- > 24 V DC execution
- > Dimmable
- > Emergency battery back-up
- > Alternative housing colors
- > Different diffusers available

TYPE	L1	L2	L3
DE95 DCC S	864	640	785
DE95 DCC L	1477	1250	1398

